



Specifications Ledvance LED  
Downlight Comfort UGR19 Aluminium  
White 30W 3600lm 55D - 930 Warm  
White | Cutout 200mm- IP44 - Best  
Colour Rendering

[View Product](#)

## General Information

|                          |                                       |
|--------------------------|---------------------------------------|
| SKU                      | 254960                                |
| EAN                      | 4099854491122                         |
| Brand                    | Ledvance                              |
| Manufacturer Name        | DL CMFT D200 P 30W MS 940 U19 WT LEDV |
| Any Lamp all-in warranty | 5 Years                               |
| Average Lifetime (h)     | 100000                                |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x26              |
| Wattage                     | 30                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 930 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 90-99             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 55                             |
| Luminous Flux (Lumen)    | 3600                           |
| Luminous Efficacy (lm/W) | 120                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | Opal                           |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 200                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 117 |
| Diameter (mm) | 215 |

## Sensor Information

Type of sensor No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process